L9 ANSWER 19 OF 29 CAPLUS COPYRIGHT 2003 ACS on STN

ACCESSION NUMBER: 1974:522709 CAPLUS

DOCUMENT NUMBER:

81:122709

TITLE:

Oil- and water-repellant material

INVENTOR(S):

Kirimoto, Kazusuke; Hayashi, Takao; Kojima, Hiroaki

APPLICATION NO. DATE

PATENT ASSIGNEE(S):

Asahi Glass Co., Ltd.

SOURCE:

Ger. Offen., 33 pp.

DOCUMENT TYPE:

PATENT NO.

CODEN: GWXXBX

Patent

LANGUAGE:

German

KIND DATE

FAMILY ACC. NUM. COUNT: 1

PATENT INFORMATION:

DE 2247182 A1 19740425 DE 1972-2247	7182 19720926
DE 2247182 B2 19750807	
DE 2247182 C3 19760311	
PRIORITY APPLN. INFO.: DE 1972-2247	182 19720926
AB The addn. of polymers prepd. from C1-18 alkyl acrylates or methacrylates	
and methylolacrylamide or methylolmethacrylamide to fluoroalkyl	
acrylate polymer oil-and waterproofing agents reduced the	
finishing costs while providing good oil and water repellency without any	
adverse effect on hand. Thus, a polymer prepd. from 73%	
CH2:CHCO2CHCH2(CF)nCF3 (a 4:3:2:1 mixt. of monomers with $n = 4,6,8$, and	
10), 25% vinyl chloride, and 2% diacetoneacrylamide was mixed with an	
equal amt. of a 95:5 butyl ***acrylate*** -N-methylolacrylamide polymer	
[27157-48-8] and mixed with water to form an ***emulsion*** contg. 1%	
polymer. A 35:65 cotton-polyester fabric was padded with the	
emulsion to provide wet add-on 80% and	dried 3 min at 100.deg. and
4 min at 150.deg The finished fabric had a soft hand as well as good	
oil and water repellency.	